

Fab 8 ACOUSTICAL FABRIC DUCTING

Fab 8

This non-insulated flexible duct produced using a tough CPE polymeric film core mechanically locked together by a corrosion resistant galvanized steel helix. This acoustically rated, self-extinguishing CPE smooth core duct is a viable solution for most heating, ventilating and air conditioning systems.

Suggested Specification

Flexible duct shall be Fabriflex® Type 8 by Flexmaster. It will be constructed of an acoustically rated CPE polymeric film core mechanically locked to a corrosion resistant external steel helix. Flexible duct connections will be listed in accordance with UL-181 and classified as Class 1 Air Duct.



- Mechanically bonded
- UL listed
- Acoustically rated
- No adhesives

- Core will not aid mold & mildew growth
- Corrosion resistant galvanized steel helix
- Extremely resilient
- Lightweight

| Material: | CPE core |
|----------------------------|--|
| Maximum Rated Velocity: | 5500 F.P.M |
| Maximum Positive Pressure: | 10" w.g. positive |
| Maximum Negative Pressure: | 5" w.g. negative 1"w.g. for 18" and 20" diameter |
| Temperature Range: | -20°F to +250°F |
| Bend Radius: | 1 x diameter |
| Available Sizes: | 3" to 20" (Larger sizes on request) |
| Standard Lengths: | 25ft |
| UL Listing: | UL-181 Class 1 Air Duct |

NOTE: This UL Class 1 product has a flame spread rating of not over 25 without evidence of continued progressive combustion and a smoke developed rating of not over 50.

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.flexmaster.com.

