



## Flexmaster®

## Gear Clamps

### Gear Clamp Solution

Offers both maximum strength and anti-shear protection, providing both a practical and cost effective solution.

Ideal for properly securing Triple Lock™ flexible duct connections.

Available in diameters ranging from 2" to 24".

Excellent for mechanical maintenance programs when service is required. The use of gear clamps with Triple Lock® flex will offer a re-usable solution eliminating the need for replacement flex. When properly used, this fully adjustable clamp will provide constant tension.

Clamps come with a 5/16" hex slotted head and 1/2" wide stainless steel band.

### Specifications

Screw: 5/16" hex-head. 410 Stainless steel.

Band: 1/2" band width. 210 Stainless steel.

Housing: 20 Stainless steel.

Rated Maximum Torque: 81 in lbs - 6.75 ft lbs - 9.15Nm

Recommended Installation Torque: 45-65 in lbs - 5.1-7.2Nm



The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: [www.novaflex.com](http://www.novaflex.com) | [www.z-flex.com](http://www.z-flex.com) | [www.flexmaster.com](http://www.flexmaster.com).

11.2020

### IN CANADA

#### Richmond Hill, Ontario

20 East Pearce Street  
Richmond Hill, ON L4B 1B7  
tel (905) 731-9411  
fax (905) 905-731-7086



Email: [sales@novaflex.com](mailto:sales@novaflex.com)  
Website: [www.novaflex.com](http://www.novaflex.com)