

Fab 4 FLEXIBLE FABRIC DUCTING

Fab 4

This extremely tough non-insulated flexible air duct is produced with a heavy fiberglass cloth with flame retardant coating which is mechanically locked together with a scuff protecting galvanized steel helix. The impact resistant UL-181 Class 1 product is shaped by the outside helix which locks together the strong duct fabric. This construction combination supplies the necessary strength to obtain a complete air duct rating, in a non-insulated form, demanded in many high pressure air distribution networks.

Flame test UL94V-0 compliant

Suggested Specification

Flexible duct shall be Fabriflex® Type 4 by Flexmaster. It will be constructed of a fiberglass cloth with a flame retardant coating which is mechanically bonded to a corrosive resistant outside metal helix. This duct shall be listed in accordance with UL-181 specification as a Class 1 Air Connector.



- Mechanically bonded
- Exterior galvanized steel helix
- Reinforced ducting
- UL Listed
- No adhesives
- Core will not aid mold & mildew growth
- Exceptional strength
- Promotes scuff resistance
- Air tight and leakproof
- Corrosive resistant helix
- Lightweight
- Tear resistant
- High pressure rated

Material:	Flame retardant coated fiberglass cloth
Maximum Rated Velocity:	5500 fpm
Maximum Positive Pressure:	25" W.G.
Maximum Negative Pressure:	Thru 12" - 10" W.G. 14" - 16" - 5" W.G. 18" - 20" - 1" W.G.
Temperature Range:	-20°F to +250°F (-30° to +120°C)
Bend Radius:	1 x diameter
Available Sizes:	3" to 20" (larger sizes on request)
Standard Lengths:	25ft
UL Listing:	UL-181 Class 1 Air Connector
Standard Lengths	25ft

NOTE: This UL Class 1 product has a flame spread rating of not over 25 without evidence of continued progressive combustion and a smoke developed rating of not over 50.

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com

05.2024