

Triple Lock® Aluminum Flexible Ducting

Triple Lock® T/L-T

An insulated air duct which is spirally wound and mechanically joined together. The inner duct is draped with thick fiberglass insulation and covered with a flame retardant non-toxic polyethylene vapour barrier. The UL-181 Class 1 product is an excellent insulated air duct for most energy efficient heating and cooling systems.

Suggested Specification

Flexible duct shall be *Triple Lock® T/L-T* by Flexmaster. The duct will be made of dead soft aluminum and manufactured in a manner to produce a three ply airtight mechanical seam. The core will be factory wrapped in fiberglass insulation and covered with a flame retardant, non-toxic polyethylene vapour barrier. This flexible insulated aluminum duct will be listed in accordance with and classified Class 1.



- Three ply mechanical airtight seam
- Manufactured from dead soft pure aluminum
- Vapour barrier
- UL listed
- Greater flexibility
- Exceptional strength
- Corrosive resistant
- Air tight and leakproof core
- Vibration deadening properties
- Lightweight, self supporting
- Low permeability barrier
- Thermal reliability

Material:	Aluminum core
Thermal Resistance:	Available: R4.2, R6, R8
Maximum Rated Velocity:	5500 fpm
Maximum Positive Pressure:	10" wg positive thru 16" diameter 6" wg positive, 18" diameter
Maximum Negative Pressure:	12" wg negative thru 16" diameter 4" negative, 18" diameter
Temperature Range	-40° to +250°F (-40°C to +121°C)
Bend Radius	1½ x diameter
Available Sizes	4" to 20"
Standard Lengths	10ft
UL Listing	Class 1

NOTE: This UL Class 1 product has a flame spread rating of not over 25 without evidence of continued progressive combustion and a smoke developed rating of not over 50.

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

05.2021