



Insulation Sleeves

Insulation Sleeves

Reduces equipment and air movement noise. Excellent thermal performance.

Factory assembled EcoTouch GREENGUARD certified, formaldehyde free insulation inner lining with polyethylene or mylar vapor barrier.

Meets guidelines for anti-bacterial and anti-moisture. Available in diameters ranging from 2" to 24".

Model INSL

Polyethylene Vapor Barrier Permeance

.10 Perm A.S.T.M E96 Procedure A

Operating Temperature range: -20°F to +250°F

Model INSM

Mylar Vapor Barrier Permeance

.05 Perm A.S.T.M E96 Procedure A

Operating Temperature Range: -20°F to +250°F

Thermal resistance: R4.2, R6, R8

Approval: ULC-S1 10, Component, Air Ducts Certified for Canada, Class 1

This ULC Class 1 product has a flame spread rating of not over 25 without evidence of continued progressive combustion and a smoke developed rating of not over 50.



The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete [Terms and Conditions of Sale](#) located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

10.2020

