

Flexmaster® Spiral Duct

Flexmaster® offers quality sheet metal products with distinct advantages and excellent value, improving system performance and enhancing overall aesthetics.

Products are manufactured in a wide range of diameters, gauges and metal alloys suitable for any HVAC application.

Spiral Duct

Unique lock formed seam and consistent calibrated tolerance combine to produce a superior quality product in a wide range of gauges to SMACNA standards.

Spiral duct is available in galvanized, aluminum, 304/316 stainless steel, in diameters ranging from 3" to 60".

Standard length: 10ft.



Flexmaster Spiral Duct Specification

The spiral duct shall be Flexmaster Spiral Duct. The duct shall be constructed in accordance with the latest SMACNA's duct construction standards for +10" water gauge pressure. Spiral duct shall be calibrated to manufacturer's published dimensional tolerance standard. Spiral seam slippage shall be prevented by means of a flat seam and a mechanically formed indentation evenly spaced along the spiral seam.

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete Terms and Conditions of Sale located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

rev 11.2020