

Novaflex®

Corrugated Dock Hose

Novaflex 3265

Corrugated Dock Hose

Specially designed for barge unloading where flexibility and ease of handling are required. Special tire cord reinforcement with dual wire helix and corrugated cover enhances the characteristics. Tube resistant to 5.5% aromatic fuels.

Fuel compatibility: Ethanol up to E85. Biodiesel up to B20.

Specifications

Tube: NBR

Reinforcement: Polyester tire cord, dual wire helix.

Cover: Black NBR/PVC corrugated

Ends: Straight.

Length 100 ft (max)

Temperature range: -30°F (-35°C) to +200°F (+93°C)



Specification Chart

Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3265BT-06000-00	6	7.20	4	30	30"	225	7.20
3265BT-08000-00	8	9.30	6	42	30"	225	10.84
3265BT-10000-00	10	11.50	6	60	30"	225	13.40
3265BT-12000-00	12	13.80	8	72	30"	225	17.25

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

05.2019

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk