



INSUL-VENT®

Double-Wall Insulated Vent Connector Kit - Insul-Vent™




Double Wall Insulated Vent Connector Kit
Insul-Vent™ includes: UL approved double-wall
length of Insul-Vent™, Appliance Connector, Universal
Connector. Please specify diameter and length at time
of order.

Single-Wall Vent Connector Kit - Single-Vent™



Single Wall Vent Connector Kit - Single-Vent™ includes: UL approved Single Wall Flex, Appliance Connector, Universal Connector. Please specify diameter and length at time of order.

Typical Installations*



Multiple Appliance B-Vent Single Appliance B-Vent

*All drawings are for illustrative purposes only. Please refer to guide for specific U.L. installation instructions. Always defer to local building codes.

U.S.A.

20 Commerce Park North, Bedford, NH 03110-6911 tel: 603.669.5136 fax: 603.669.0309

www.z-flex.com email sales@z-flex.com

Z-Flex Connector System

This cULus listed connector meets the requirements of NFPA 54. ANSI 2231 and NFPA 211.

Usage

Double-wall flexible vent connector for connecting one or more appliances to double-wall Type B gas vents and listed Z-Flex liners. Use only with Category I appliances listed for use with Type B gas vent.

Warning

Do not enclose. Do no pass through walls, floors or ceilings.

CANADA

452 Attwell Drive, Etobicoke, ON M9W 5C3 tel: 416.679.0045 fax: 416.679.0051